

WHAT IS CLAIMED IS:

1. A flexible stent for implantation in a body lumen and expandable from a contracted condition to an expanded condition, comprising:

5 a plurality of adjacent cylindrical elements which are expandable in the radial direction and arranged in alignment along a longitudinal stent axis;

the cylindrical elements formed in a serpentine wave pattern transverse to the longitudinal axis and containing a plurality of alternating peaks and valleys;

10 at least one interconnecting member extending between adjacent cylindrical elements and connecting them to one another;

at least one reinforcing member extending across a width of the alternating peaks and valleys;

15 the serpentine pattern containing varying degrees of curvature in regions of the peaks and valleys adapted so that radial expansion of the adjacent cylindrical elements is substantially uniform around their circumferences during expansion of the stent from its contracted condition to its expanded condition.

2. The stent of claim 1, wherein the stent further comprises at least one reinforcing member extending across a width of each of the alternating peaks and valleys.

3. The stent of claim 1, wherein the interconnecting member connects a valley of one cylindrical element with a valley of an adjacent cylindrical element.

4. The stent of claim 1, wherein the interconnecting member connects a reinforcing member of a

09843319.050304
T02050" 5T334860

valley of one cylindrical element with a valley of an adjacent cylindrical element.

5. (1) The stent of claim 3, wherein the interconnecting member is unitary with the valley of one cylindrical element and the valley of the adjacent cylindrical element.

6. The stent of claim 1, wherein the reinforcing member is curved opposite to the respective peaks and valleys.

7. The stent of claim 1, wherein the alternating peaks and valleys are further comprised of straight-length struts intersecting at an angle, and wherein the reinforcing member engages the intersecting struts at bend points.

8. The stent of claim 7, wherein each bend point is a portion of the strut having reduced material to facilitate bending.

9. The stent of claim 1, wherein the alternating peaks and valleys are further comprised of elongated straight-length struts intersecting at an angle, and wherein the reinforcing member engages the intersecting struts at bend
5 points of the elongated struts.

10. The stent of claim 1, wherein the reinforcing member is comprised of a first quarter turn that transitions into a half turn, which transitions into a second quarter turn.

RECEIVED 6 FEB 1960

11. The stent of claim 1, wherein an intersection of the reinforcing member and the peaks and valleys is rounded.

12. The stent of claim 1, wherein an intersection of the reinforcing member and the peaks and valleys is angular.

13. The stent of claim 1, wherein the reinforcing member is further comprised of an enlarged area integrated into the peak and valley.

14. The stent of claim 1, wherein the reinforcing member is further comprised of an enlarged area integrated into the peak and valley having slits therethrough.

15. The stent of claim 1, wherein said stent is formed of a biocompatible material selected from the group consisting of stainless steel, tungsten, tantalum, super-elastic NiTi alloys, and thermoplastic polymers.

16. The stent of claim 1, wherein the stent is formed from a single piece of tubing.

17. The stent of claim 1, wherein the stent is coated with a biocompatible coating.

18. A longitudinally flexible stent for implanting in a body lumen and expandable from a contracted condition to an expanded condition, comprising:

09849815 050304

5 a plurality of adjacent cylindrical elements which
are independently expandable in the radial direction and
arranged in alignment along a longitudinal stent axis;

the cylindrical elements formed in a serpentine wave
pattern transverse to the longitudinal axis and containing
alternating peaks and valleys;

10 at least one interconnecting member extending between
adjacent cylindrical elements and connecting them to one
another;

a reinforcing member extending across each peak and
valley; and

15 the serpentine wave pattern configured in size and
shape so that the cylindrical elements generally expand in a
uniform manner around their circumferences during expansion of
the stent from its contracted condition to its expanded
condition.

19. The stent of claim 18, wherein within a single
cylindrical element, the serpentine wave pattern includes a
sequence containing a peak, a valley, a peak, a valley, a
valley, and a peak.

20. The stent of claim 18, wherein said at least one
interconnecting member connects a valley of one cylindrical
element with a valley of an adjacent cylindrical element.

21. The stent of claim 18, wherein the stent is
formed of a biocompatible material selected from the group
consisting of stainless steel, tungsten, tantalum, super-
elastic NiTi alloys, and thermoplastic polymers.

22. A method for constructing a flexible stent for
implantation in a body lumen wherein the stent is expandable

0984819 050304
RECEIVED

Coulam et al.		Coulam et al.	
Study	Year	Study	Year
1	1998	1	1998
2	1998	2	1998
3	1998	3	1998
4	1998	4	1998
5	1998	5	1998
6	1998	6	1998
7	1998	7	1998
8	1998	8	1998
9	1998	9	1998
10	1998	10	1998
11	1998	11	1998
12	1998	12	1998
13	1998	13	1998
14	1998	14	1998
15	1998	15	1998
16	1998	16	1998
17	1998	17	1998
18	1998	18	1998
19	1998	19	1998
20	1998	20	1998
21	1998	21	1998
22	1998	22	1998
23	1998	23	1998
24	1998	24	1998
25	1998	25	1998
26	1998	26	1998
27	1998	27	1998
28	1998	28	1998
29	1998	29	1998
30	1998	30	1998
31	1998	31	1998
32	1998	32	1998
33	1998	33	1998
34	1998	34	1998
35	1998	35	1998
36	1998	36	1998
37	1998	37	1998
38	1998	38	1998
39	1998	39	1998
40	1998	40	1998
41	1998	41	1998
42	1998	42	1998
43	1998	43	1998
44	1998	44	1998
45	1998	45	1998
46	1998	46	1998
47	1998	47	1998
48	1998	48	1998
49	1998	49	1998
50	1998	50	1998
51	1998	51	1998
52	1998	52	1998
53	1998	53	1998
54	1998	54	1998
55	1998	55	1998
56	1998	56	1998
57	1998	57	1998
58	1998	58	1998
59	1998	59	1998
60	1998	60	1998
61	1998	61	1998
62	1998	62	1998
63	1998	63	1998
64	1998	64	1998
65	1998	65	1998
66	1998	66	1998
67	1998	67	1998
68	1998	68	1998
69	1998	69	1998
70	1998	70	1998
71	1998	71	1998
72	1998	72	1998
73	1998	73	1998
74	1998	74	1998
75	1998	75	1998
76	1998	76	1998
77	1998	77	1998
78	1998	78	1998
79	1998	79	1998
80	1998	80	1998
81	1998	81	1998
82	1998	82	1998
83	1998	83	1998
84	1998	84	1998
85	1998	85	1998
86	1998	86	1998
87	1998	87	1998
88	1998	88	1998
89	1998	89	1998
90	1998	90	1998
91	1998	91	1998
92	1998	92	1998
93	1998	93	1998
94	1998	94	

5

10

15

20

23. The process of claim 18, wherein the process further comprises the step of connecting the interconnecting member between a valley of one cylindrical element with a valley of an adjacent cylindrical element.